


## FEATURES

- 30g or 100g operating spring force
- 30 milliOhms contact resistance
- 4 GHz Bandwidth (Calculated)
- 5 Amp DC Current Max

## GENERAL DESCRIPTION


The E5509 spring probe from Signal Integrity Inc. is designed to meet the rigorous test requirements driven by high power and high reliability requirements. Along with speed and accuracy, these probes are designed to operate at pitches to 1.0mm, specifically for the semiconductor probe tower applications these markets demand.



## SERIES E5509 MODELS: ORDERING INFORMATION

E5509 Series Interface Pin					
Model	Length Operating / initial inch [mm]	DUT Plunger and Plating	Interface Plunger	Spring	Operating Spring Force
E5509-A1	.680 [17.27] / .730 [18.54]	Crown - Gold	Crown	Stainless Steel	100 Grams
E5509-B2		Conic - Gold	Conic		
E5509-C3	.670 [17.00] / .730 [18.54]	Crown - Gold	Crown		30 Grams
E5509-D4		Conic - Gold	Conic		

MECHANICAL DIMENSIONS  
INCHES [MM]



Signal Integrity, Inc.  
104 County Street, Ste. 210, Attleboro, MA 02703  
Tel: 1-508-226-6480 Fax: 1-508-226-6488 Internet: [www.signalin.com](http://www.signalin.com)

Signal Integrity makes no representation that the use of its products described herein, or the use of other technical information contained herein, will not infringe on existing or future patent rights. The descriptions contained herein do not imply the granting of licenses to make, use, or sell equipment constructed in accordance therewith. Specifications are subject to change without notice.